



TECHNICAL SPECIFICATIONS

NOVITA® 2302101 – Vellum / Hotmelt / Yellow Glassine

FACESTOCK

A white gloss, woodfree, one side coated, printing paper

- Description** A white gloss
- Printing Process** Suitable for all kind of printing process especially flexo, letterpress, offset, screen printing and hot stamping.
- Applications** Typical applications include labels for use in many industries e.g. cosmetics, food, beverage and pharmaceutical. Also due to its flexible nature suited for curved surfaces.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	80	±4
Thickness	ILKAY 017	µm	65	±4

ADHESIVE

H1000

- Description** This type of permanent rubber based adhesive provides excellent tack and adhesion on a wide variety of surfaces. Also it has a higher peeling value. It is suitable for wide range of temperature values. It has a good performance at lower temperature.
- Shelf Life** Two years, stored at 22°C / 50% RH.

Property	Standart	Units	Value	Tolerance
Adhesion (Peel 90°/Steel)	ILKAY 003	N/25 mm	10	± 1
Loop Tack (Steel)	ILKAY 001	N/25 mm	N/A	± 3
Minimum labelling temperature		°C	+0	
Minimum service temperature		°C	-20	
Minimum service temperature		°C	+80	

LINER

Yellow Glassine

- Description** A yellow, highly calendered siliconized glassine paper.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	60	±4
Thickness	ILKAY 017	µm	53	±4

- Values are subject to change without notice.
- The technical information in this document are based on our knowledge and experience, but should only be considered as a general.

