



TECHNICAL SPECIFICATIONS

NOVITA® 10105 – Gloss Coated / 0603 / Yellow Glassine

FACESTOCK

Gloss Coated

Description Gloss coated woodfree paper.

Printing Process Suitable for printing in all types of flexo and letterpress systems, offset, screen printing and hot stamping.

Applications High resolution standart gloss label for multicolour printing; used in food and beverage industry.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	78	±2
Thickness	ILKAY 017	µm	65	±2

ADHESIVE

0603

Description A removable, emulsion acrylic based adhesive. Good tack and adhesion in combination with clean removability from most substrates.

Shelf Life Two years, stored at 22°C / 50% RH.

Property	Standart	Units	Value	Tolerance
Adhesion (Peel 90°/Steel)	ILKAY 003	N/25 mm	1,5	minimum
Loop Tack (Steel)	ILKAY 001	N/25 mm	1,5	minimum
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-30	
Minimum service temperature		°C	+80	

LINER

Yellow Glassine

Description Supercalendered transparent glassine paper. Especially used for automatic labelling applications and other systems.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	62	±2
Thickness	ILKAY 017	µm	40	±2

- Values are subject to change without notice.
- The technical information in this document are based on our knowledge and experience, but should only be considered as a general.