



# TECHNICAL SPECIFICATIONS

## NOVITA® 4203402 – PP White / A3000 / CCK

### FACESTOCK

#### PP White

- Description** Glossy biaxially-oriented polypropylene with printreceptive topcoating. Good temperature and chemicals resistance.
- Printing Process** Suitable for printing in all types of flexo and letterpress systems, offset, screen printing and hot stamping.
- Applications** High quality labelling of cosmetics and perfumes where durability and resistance to moisture and chemicals are required.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m <sup>2</sup>	46	±2
Thickness	ILKAY 017	µm	50	±2

### ADHESIVE

#### A 3000

- Description** General use permanent adhesive for papers and films. High initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates.
- Shelf Life** Two years, stored at 22°C / 50% RH.

Property	Standart	Units	Value	Tolerance
Adhesion (Peel 90°/Steel)	ILKAY 003	N/25 mm	6	± 1
Loop Tack	ILKAY 001	N/25 mm	15	± 3
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Minimum service temperature		°C	+80	

### LINER

#### CCK 127

- Description** Good dimensional stability and layflatness, one-side silicon paper. CCK papers are suitable for even the most demanding and diverse label converting processes.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m <sup>2</sup>	127	±2
Thickness	ILKAY 017	µm	125	±5

- Values are subject to change without notice.
- The technical information in this document are based on our knowledge and experience, but should only be considered as a general.

