



TECHNICAL SPECIFICATIONS

NOVITA® 20104 – Gloss Coated / 0602 / CCK 80

FACESTOCK

Gloss Coated

Description Gloss coated woodfree paper.

Printing Process Suitable for offset print.

Applications High resolution standart gloss label for multicolour printing; used in food, furniture industry.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	78	±2
Thickness	ILKAY 017	µm	65	±2

ADHESIVE

0602

Description A permanent hotmelt rubber based adhesive. Excellent tack and adhesion on a wide variety of substrates, including slightly rough and curved substrates.

Shelf Life Two years, stored at 22°C / 50% RH.

Property	Standart	Units	Value	Tolerance
Adhesion (Peel 90°/Steel)	ILKAY 003	N/25 mm	8	minimum
Loop Tack (Steel)	ILKAY 001	N/25 mm	8	minimum
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-40	
Minimum service temperature		°C	+70	

LINER

CCK 80

Description Good dimensional stability and layflatness, one-side silicon paper. CCK papers are suitable for even the most demanding and diverse label converting processes. Liner has been slitted every 5 cm in this product.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	80	±2
Thickness	ILKAY 017	µm	75	±2

- Values are subject to change without notice.
- The technical information in this document are based on our knowledge and experience, but should only be considered as a general.

