



TECHNICAL SPECIFICATIONS

NOVITA® 10602 – PP Transparent / 0601 / CCK 125

FACESTOCK

PP Transparent

- Description** Glossy biaxially-oriented polypropylene with printreceptive topcoating. Good temperature and chemicals resistance.
- Printing Process** Suitable for printing in all types of flexo and letterpress systems, offset, screen printing and hot stamping.
- Applications** High quality labelling of cosmetics and perfumes where durability and resistance to moisture and chemicals are required.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	49	±2
Thickness	ILKAY 017	µm	50	±2

ADHESIVE

0601

- Description** General use permanent adhesive for papers and films. High initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates.
- Shelf Life** Two years, stored at 22°C / 50% RH.

Property	Standart	Units	Value	Tolerance
Adhesion (Peel 90°/Steel)	ILKAY 003	N/25 mm	7	minimum
Loop Tack	ILKAY 001	N/25 mm	5	minimum
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Minimum service temperature		°C	+80	

LINER

CCK 125

- Description** Good dimensional stability and layflatness, one-side silicon paper. CCK papers are suitable for even the most demanding and diverse label converting processes.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	125	±2
Thickness	ILKAY 017	µm	128	±2

- Values are subject to change without notice.
- The technical information in this document are based on our knowledge and experience, but should only be considered as a general.