



TECHNICAL SPECIFICATIONS

NOVITA® 10904 – Coloured Uncoated Fluorescent Orange / 0601 / Yellow Glassine

FACESTOCK

Coloured Uncoated Fluorescent Orange

Description Uncoated woodfree paper with fluorescent coloured.

Printing Process Suitable for flexo, offset and letterpress.

Applications Eye-catching labels for pricing, display, promotions and warning signs.

| Property | Standart | Units | Value | Tolerance |
|-----------|-----------|------------------|-------|-----------|
| Substance | ILKAY 011 | g/m ² | 80 | ±2 |
| Thickness | ILKAY 017 | µm | 90 | ±2 |

ADHESIVE

0601

Description General use permanent adhesive for papers and films. High initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates.

Shelf Life Two years, stored at 22°C / 50% RH.

| Property | Standart | Units | Value | Tolerance |
|-------------------------------|-----------|---------|-------|-----------|
| Adhesion (Peel 90°/Steel) | ILKAY 003 | N/25 mm | 7 | minimum |
| Loop Tack | ILKAY 001 | N/25 mm | 5 | minimum |
| Minimum labelling temperature | | °C | +5 | |
| Minimum service temperature | | °C | -20 | |
| Minimum service temperature | | °C | +80 | |

LINER

Yellow Glassine

Description Supercalendered transparent glassine paper. Especially used for automatic labelling applications and other systems.

| Property | Standart | Units | Value | Tolerance |
|-----------|-----------|------------------|-------|-----------|
| Substance | ILKAY 011 | g/m ² | 62 | ±2 |
| Thickness | ILKAY 017 | µm | 40 | ±2 |

- Values are subject to change without notice.
- The technical information in this document are based on our knowledge and experience, but should only be considered as a general.