



TECHNICAL SPECIFICATIONS

NOVITA® 10203 – Eco Thermal / 0603 / Yellow Glassine

FACESTOCK

Eco Thermal

- Description** Thermo sensitive paper.
- Printing Process** Suitable for UV and water-based flexo, UV offset, barcod printers.
- Applications** Used in variable information labelling in dry environments; price marking, barcodes, shipping forms etc. Label is removable from the substrate.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	75	±2
Thickness	ILKAY 017	µm	72	±2

ADHESIVE

0603

- Description** A removable, emulsion acrylic based adhesive. Good tack and adhesion in combination with clean removability from most substrates.
- Shelf Life** Two years, stored at 22°C / 50% RH.

Property	Standart	Units	Value	Tolerance
Adhesion (Peel 90°/Steel)	ILKAY 003	N/25 mm	1,5	minimum
Loop Tack (Steel)	ILKAY 001	N/25 mm	1,5	minimum
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-30	
Minimum service temperature		°C	+80	

LINER

Yellow Glassine

- Description** Supercalendered transparent glassine paper. Especially used for automatic labelling applications and other systems.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	62	±2
Thickness	ILKAY 017	µm	40	±2

- Values are subject to change without notice.
- The technical information in this document are based on our knowledge and experience, but should only be considered as a general.