



TECHNICAL SPECIFICATIONS

NOVITA® 10604 – PP Transparent / 0603 / Yellow Glassine

FACESTOCK

PP Transparent

Description Glossy biaxially-oriented polypropylene with printreceptive topcoating. Good temperature and chemicals resistance.

Printing Process Suitable for printing in all types of flexo and letterpress systems, offset, screen printing and hot stamping.

Applications High quality labelling of cosmetics and parfumes where durability and resistance to moisture and chemicals are required. Label is removable from the substrate.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	49	±2
Thickness	ILKAY 017	µm	50	±2

ADHESIVE

0603

Description A removable, emulsion acrylic based adhesive. Good tack and adhesion in combination with clean removability from most substrates.

Shelf Life Two years, stored at 22°C / 50% RH.

Property	Standart	Units	Value	Tolerance
Adhesion (Peel 90°/Steel)	ILKAY 003	N/25 mm	1,5	minimum
Loop Tack (Steel)	ILKAY 001	N/25 mm	1,5	minimum
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-30	
Minimum service temperature		°C	+80	

LINER

Yellow Glassine

Description Supercalendered transparent glassine paper. Especially used for automatic labelling applications and other systems.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	62	±2
Thickness	ILKAY 017	µm	40	±2

- Values are subject to change without notice.
- The technical information in this document are based on our knowledge and experience, but should only be considered as a general.

