



TECHNICAL SPECIFICATIONS

NOVITA® 20102 – Gloss Coated / 0601 / CCK 80 Back Slitted

FACESTOCK

Gloss Coated

Description Gloss coated woodfree paper.

Printing Process Suitable for offset print.

Applications High resolution standart gloss label for multicolour printing; used in food, furniture industry.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	78	±2
Thickness	ILKAY 017	µm	65	±2

ADHESIVE

0601

Description General use permanent adhesive for papers and films. High initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates.

Shelf Life Two years, stored at 22°C / 50% RH.

Property	Standart	Units	Value	Tolerance
Adhesion (Peel 90°/Steel)	ILKAY 003	N/25 mm	7	minimum
Loop Tack	ILKAY 001	N/25 mm	5	minimum
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Minimum service temperature		°C	+80	

LINER

CCK 80

Description Good dimensional stability and layflatness, one-side silicon paper. CCK papers are suitable for even the most demanding and diverse label converting processes. Liner has been slitted every 5 cm in this product.

Property	Standart	Units	Value	Tolerance
Substance	ILKAY 011	g/m ²	80	±2
Thickness	ILKAY 017	µm	75	±2

- Values are subject to change without notice.

- The technical information in this document are based on our knowledge and experience, but should only be considered as a general.