



TECHNICAL SPECIFICATIONS

NOVITA® 2102402 – Wood Free / Hotmelt / CCK 127

FACESTOCK

A woodfree uncoated White paper.

- Description** A woodfree uncoated
- Printing Process** Suitable for all kind of printing process especially flexo,letterpress,offset, screen printing and hot stamping.
- Applications** Typical applications include labels for use in many industries e.g. cosmetics, food,beverange and pharmaceutical. Also due to its flexible nature suited for curved surfaces.

| Property | Standart | Units | Value | Tolerance |
|-----------|-----------|------------------|-------|-----------|
| Substance | ILKAY 011 | g/m ² | 80 | ±4 |
| Thickness | ILKAY 017 | µm | 75 | ±4 |

ADHESIVE

H1000

- Description** This type of permanent rubber based adhesive provides excellent tack and adhesion on a wide variety of surfaces. Also it as a higher peeling value. It is suitable for wide range of temperature values. It has a good performance at lower temperature.
- Shelf Life** Two years, stored at 22°C / 50% RH.

| Property | Standart | Units | Value | Tolerance |
|-------------------------------|-----------|---------|-------|-----------|
| Adhesion (Peel 90°/Steel) | ILKAY 003 | N/25 mm | 10 | ± 1 |
| Loop Tack (Steel) | ILKAY 001 | N/25 mm | N/A | ± 3 |
| Minimum labelling temperature | | °C | +0 | |
| Minimum service temperature | | °C | -20 | |
| Minimum service temperature | | °C | +80 | |

LINER

White CCK

- Description** A yellow, highly calendered siliconized glassine paper.

| Property | Standart | Units | Value | Tolerance |
|-----------|-----------|------------------|-------|-----------|
| Substance | ILKAY 011 | g/m ² | 127 | ±4 |
| Thickness | ILKAY 017 | µm | 125 | ±4 |

- Values are subject to change without notice.
- The technical information in this document are based on our knowledge and experience, but should only be considered as a general.

